

10HX230



LF 10" - 250 W - 96 dB - 8 Ohm

HF 30 W - 107 dB - 8 Ohm

NOMINAL SPECIFICATIONS

Nom. Diameter	250 mm (10 in)
Overall Diameter	261 mm (10.28 in)
Bolt Circle Diameter	246 mm (9.69 in)
Baffle Cutout Diameter	230 mm (9.06 in)
Depth	136.5 mm (5.37 in)
Flange and Gasket Thickness	12 mm (0.47 in)
Net Weight	5 kg (11.0 lb)
Shipping Box (Single Carton Box)	282 x 280 x 140 mm (9.3 x 9.3 x 6.1 in)
Shipping Weight	5.4 kg (11.9 lb)

PART NUMBER

Push Terminals - 8 Ohm Version	02504277
--------------------------------	----------

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) HF Sensitivity averaged within the frequency range
- (4) 12 dB/oct or higher slope high-pass filter
- (5) Treated Polycotton
- (6) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (7) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

	LF	HF
Nom. Impedance	8 Ohm	8 Ohm
Minimum Impedance	6.4 Ohm	6.9 Ohm
AES Power Handling (1)	250 W	30 W
Max Power Handling (2)	500 W	60 W
Sensitivity (1W/1m) (3)	96 dB	107 dB
Frequency Range	65-4000 Hz	1500-20000 Hz
Voice Coil Diameter	65 mm (2.56 in)	37 mm (1.46 in)
Winding Material	Al	Al
Former Material	Glass Fiber	Kapton
Winding Depth	17.4 mm (0.69 in)	2.1 mm (0.08 in)
Magnetic Gap Depth	8 mm (0.31 in)	2.6 mm (0.10 in)
Flux Density	1.15 T	1.85 T
Min. Cross. Freq. (4)	-	1.7 kHz
Dispersion Angle	-	110°
Diaphragm Material	-	Ketone Polymer
Diaphragm Shape	-	Annular
Magnet	Ferrite Ring	Neodymium Ring
Basket Material	Aluminum	-
Demodulation	Aluminum Ring	-
Cone Surround (5)	Triple Roll	-
NET Air Volume filled by Loudspeaker	1.5 dm ³ (0.053 ft ³)	-
Spider Profile	1x variable height waves	-

THIELE & SMALL PARAMETERS

Fs	65 Hz
Re [LF]	5.3 Ohm
Re [HF]	5.5 Ohm
Qes	0.42
Qms	5.8
Qts	0.39
Vas	30.5 dm ³ (1.08 ft ³)
Sd	347 cm ² (53.71 in ²)
Xmax (6)	7.37 mm
Xdamage (7)	14.8 mm
Mms	33.0 g
Bl	13.1 N/A
Le	0.54 mH
Mmd	25.7 g
Cms	0.18 mm/N
Rms	2.4 kg/s
Eta Zero	1.95 %
EBP	155 Hz

