

12HX240



LF 12" - 250 W - 97 dB - 8 Ohm

HF 30 W - 107 dB - 8 Ohm

NOMINAL SPECIFICATIONS

Nom. Diameter	300 mm (12 in)
Overall Diameter	316 mm (12.44 in)
Bolt Circle Diameter	298.5 mm (11.75 in)
Baffle Cutout Diameter	280 mm (11.02 in)
Depth	162 mm (6.38 in)
Flange and Gasket Thickness	12 mm (0.47 in)
Net Weight	4.2 kg (9.3 lb)
Shipping Box (Single Carton Box)	350 x 346 x 216 mm (13.8 x 13.6 x 8.5 in)
Shipping Weight	5 kg (11.0 lb)

PART NUMBER

Push Terminals - 8 Ohm Version	03004319
Recone Kit LF - 8 Ohm Version	R3004278
Recone Kit HF - 8 Ohm Version	R0374049

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) HF Sensitivity averaged within the frequency range
- (4) 12 dB/oct or higher slope high-pass filter
- (5) Treated Polycotton
- (6) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (7) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

	LF	HF
Nom. Impedance	8 Ohm	8 Ohm
Minimum Impedance	6.4 Ohm	6.8 Ohm
AES Power Handling (1)	250 W	30 W
Max Power Handling (2)	500 W	60 W
Sensitivity (1W/1m) (3)	97 dB	107 dB
Frequency Range	55-5000 Hz	1500-20000 Hz
Voice Coil Diameter	65 mm (2.56 in)	37 mm (1.46 in)
Winding Material	Al	Al
Former Material	Glass Fiber	Kapton
Winding Depth	17.4 mm (0.69 in)	2.1 mm (0.08 in)
Magnetic Gap Depth	8 mm (0.31 in)	2.6 mm (0.10 in)
Flux Density	1.25 T	1.85 T
Min. Cross. Freq. (4)	-	1.7 kHz
Dispersion Angle	-	100°
Diaphragm Material	-	Ketone Polymer
Diaphragm Shape	-	Annular
Magnet	Neodymium Ring	Neodymium Ring
Basket Material	Aluminum	-
Demodulation	Aluminum Ring	-
Cone Surround (5)	Triple Roll	-
NET Air Volume filled by Loudspeaker	1.9 dm ³ (0.067 ft ³)	-
Spider Profile	1x variable height waves	-

THIELE & SMALL PARAMETERS

Fs	56 Hz
Re [LF]	5.3 Ohm
Re [HF]	5.5 Ohm
Qes	0.38
Qms	11.3
Qts	0.37
Vas	61.1 dm ³ (2.16 ft ³)
Sd	539 cm ² (83.55 in ²)
Xmax (6)	7.37 mm
Xdamage (7)	17.4 mm
Mms	53.6 g
Bl	16 N/A
Le	0.45 mH
Mmd	39.5 g
Cms	0.15 mm/N
Rms	1.7 kg/s
Eta Zero	2.67 %
EBP	147 Hz

