

6PR110



6" - 150 W - 96 dB - 8 Ohm

NOMINAL SPECIFICATIONS

Nominal Diameter	160 mm (6 in)
Overall Diameter	186.5/162 mm (7.34/6.37 in)
Bolt Circle Diameter	172 mm (6.77 in)
Baffle Cutout Diameter	147 mm (5.79 in)
Depth	80 mm (3.15 in)
Flange and Gasket Thickness	9.5 mm (0.37 in)
Net Weight	2.2 kg (4.9 lb)
Shipping Box (Single Carton Box)	190 x 185 x 103 mm (7.5 x 7.3 x 4.1 in)
Shipping Weight	2.4 kg (5.3 lb)

PART NUMBER

Faston Terminals - 8 Ohm Version	01604091
----------------------------------	----------

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	7 Ohm
AES Power Handling (1)	150 W
Maximum Power Handling (2)	300 W
Sensitivity (1W/1m)	96 dB
Frequency Range	100-6000 Hz
Voice Coil Diameter	37 mm (1.46 in)
Winding Material	Al
Former Material	Kapton
Winding Depth	7.5 mm (0.30 in)
Magnetic Gap Depth	6 mm (0.24 in)
Flux Density	1.35 T
Magnet	Ferrite Ring
Basket Material	Aluminum
Demodulation	No
Cone Surround (3)	Half Roll
NET Air Volume filled by Loudspeaker	0.7 dm ³ (0.025 ft ³)
Spider Profile	1x constant height waves

THIELE & SMALL PARAMETERS

Fs	100 Hz
Re	6 Ohm
Qes	0.60
Qms	4.2
Qts	0.53
Vas	5.6 dm ³ (0.20 ft ³)
Sd	137 cm ² (21.28 in ²)
Xmax (4)	2.75 mm
Xdamage (5)	11.6 mm
Mms	12.0 g
Bl	8.5 N/A
Le	0.22 mH
Mmd	10.2 g
Cms	0.20 mm/N
Rms	1.8 kg/s
Eta Zero	0.86 %
EBP	167 Hz

