

8PR155



8" - 200 W - 97 dB - 8 Ohm

NOMINAL SPECIFICATIONS

Nominal Diameter	200 mm (8 in)
Overall Diameter	223.7/207.9 mm (8.81/8.18 in)
Bolt Circle Diameter	210 mm (8.27 in)
Baffle Cutout Diameter	183 mm (7.20 in)
Depth	98.5 mm (3.88 in)
Flange and Gasket Thickness	10.8 mm (0.43 in)
Net Weight	4.3 kg (9.5 lb)
Shipping Box (Single Carton Box)	235 x 235 x 155 mm (9.3 x 9.3 x 6.1 in)
Shipping Weight	4.6 kg (10.1 lb)

PART NUMBER

Faston Terminals - 8 Ohm Version	02004172
Recone Kit - 8 Ohm Version	R2004172

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4) $X_{max} = ((winding\ depth - magnetic\ gap\ depth)/2) + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	6.3 Ohm
AES Power Handling (1)	200 W
Maximum Power Handling (2)	400 W
Sensitivity (1W/1m)	97 dB
Frequency Range	80-6300 Hz
Voice Coil Diameter	52 mm (2 in)
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	9.8 mm (0.39 in)
Magnetic Gap Depth	8 mm (0.31 in)
Flux Density	1.3 T
Magnet	Ferrite Ring
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround (3)	Triple Roll
NET Air Volume filled by Loudspeaker	1.06 dm ³ (0.037 ft ³)
Spider Profile	1x variable height waves

THIELE & SMALL PARAMETERS

Fs	85 Hz
Re	5.3 Ohm
Qes	0.39
Qms	8.8
Qts	0.37
Vas	9.4 dm ³ (0.33 ft ³)
Sd	217 cm ² (33.67 in ²)
Xmax (4)	3.57 mm
Xdamage (5)	10.65 mm
Mms	24.5 g
Bl	13.4 N/A
Le	0.41 mH
Mmd	20.9 g
Cms	0.14 mm/N
Rms	1.5 kg/s
Eta Zero	1.45 %
EBP	218 Hz

