PROFESSIONAL LOUDSPEAKERS

8RS350

8" 300 W - 90 dB - 8 Ohm



NOMINAL SPECIFICATIONS

Nominal Diameter	200 mm (8 in)
Overall Diameter	223.7/207.9 mm (8.81/8.18 in)
Bolt Circle Diameter	210 mm (8.27 in)
Baffle Cutout Diameter	183 mm (7.20 in)
Depth	106.5 mm (4.19 in)
Flange and Gasket Thickness	16 mm (0.63 in)
Net Weight	**4.1 kg (9.0 lb)**
Shipping Box (Single Carton Box)	235 x 235 x 155 mm (9.3 x 9.3 x 6.1 in)
Shipping Weight	4.8 kg (10.6 lb)

PART NUMBER

Push Terminals - 8 Ohm Version	02004384

NOTES:

(1) 2 Hours Test According to AES 2-1984 Rev. 2003

(2) Maximum power is defined as 3dB greater than nominal power.

(3) NBR (Rubber)

(4) Xmax= [(winding depth - magnetic gap depth)/2] + (magnetic gap depth/3)


(5) Maximum excursion before permanent damage


TECHNICAL PARAMETERS


Nominal Impedance	8 Ohm
Minimum Impedance	6.2 Ohm
AES Power Handling **(1)**	300 W
Maximum Power Handling (2)	**600 W**
Sensitivity (1W/1m)	**90 dB**
Frequency Range	50÷6300 Hz
Voice Coil Diameter	**65 mm (2.56 in)**
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	17.4 mm (0.69 in)
Magnetic Gap Depth	**8 mm (0.31 in)**
Flux Density	1.2 T
Magnet	Ferrite Ring
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround **(3)**	Half Roll
NET Air Volume filled by Loudspeaker	1.04 dm^3 (0.037 ft^3)
Spider Profile	1x constant height waves

THIELE & SMALL PARAMETERS

Fs	42 Hz
Re	5.3 Ohm
Qes	0.31
Qms	6.9
Qts	0.30
Vas	23.7 dm^3 (0.84 ft^3)
Sd	226 cm^2 (35.03 in^2)
Xmax **(4)**	7.37 mm
Xdamage **(5)**	16.85 mm
Mms	43.3 g
Bl	13.9 N/A
Le	0.6 mH
Mmd	39.5 g
Cms	0.33 mm/N
Rms	1.7 kg/s
Eta Zero	0.54 %
EBP	134 Hz







©Copyright 2026 **Faital S.p.A.** • All rights reserved.