

# 12PR300



12" - 300 W - 97 dB - 4 Ohm

### NOMINAL SPECIFICATIONS

Nominal Diameter	300 mm (12 in)
Overall Diameter	315.2 mm (12.44 in)
Bolt Circle Diameter	298.5 mm (11.75 in)
Baffle Cutout Diameter	283 mm (11.14 in)
Depth	140.6 mm (5.54 in)
Flange and Gasket Thickness	12.1 mm (0.48 in)
<b>Net Weight</b>	<b>2.5 kg (5.5 lb)</b>
Shipping Box (Single Carton Box)	350 x 346 x 216 mm (13.8 x 13.6 x 8.5 in)
Shipping Weight	3.3 kg (7.2 lb)

### PART NUMBER

Push Terminals - 4 Ohm Version	03003957
Recone Kit - 4 Ohm Version	R3003957

### NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4)  $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

### TECHNICAL PARAMETERS

Nominal Impedance	4 Ohm
Minimum Impedance	4 Ohm
AES Power Handling (1)	300 W
<b>Maximum Power Handling (2)</b>	<b>600 W</b>
<b>Sensitivity (1W/1m)</b>	<b>97 dB</b>
Frequency Range	50-5000 Hz
<b>Voice Coil Diameter</b>	<b>65 mm (2.56 in)</b>
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	12.5 mm (0.49 in)
<b>Magnetic Gap Depth</b>	<b>8 mm (0.31 in)</b>
Flux Density	1.25 T
Magnet	Neodymium Slug
Basket Material	Aluminum
Demodulation	No
Cone Surround (3)	M-Roll
NET Air Volume filled by Loudspeaker	1.9 dm <sup>3</sup> (0.067 ft <sup>3</sup> )
Spider Profile	1x variable height waves

### THIELE & SMALL PARAMETERS

Fs	50 Hz
Re	3.3 Ohm
Qes	0.42
Qms	19.4
Qts	0.41
Vas	73.9 dm <sup>3</sup> (2.61 ft <sup>3</sup> )
Sd	533 cm <sup>2</sup> (82.62 in <sup>2</sup> )
Xmax (4)	4.92 mm
Xdamage (5)	14 mm
Mms	54.4 g
Bl	11.8 N/A
Le	0.46 mH
Mmd	40.5 g
Cms	0.19 mm/N
Rms	0.9 kg/s
Eta Zero	2.21 %
EBP	119 Hz

