

# 15PR300



15" - 300 W - 97 dB - 8 Ohm

## NOMINAL SPECIFICATIONS

Nominal Diameter	380 mm (15 in)
Overall Diameter	393 mm (15.47 in)
Bolt Circle Diameter	374 mm (14.72 in)
Baffle Cutout Diameter	356 mm (14.02 in)
Depth	165 mm (6.50 in)
Flange and Gasket Thickness	13.1 mm (0.52 in)
<b>Net Weight</b>	<b>3.2 kg (7.1 lb)</b>
Shipping Box (Single Carton Box)	430 x 427 x 236 mm (16.9 x 16.8 x 9.3 in)
Shipping Weight	4.3 kg (9.5 lb)

## PART NUMBER

Push Terminals - 8 Ohm Version	03804397
--------------------------------	----------

## NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4)  $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

## TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	6 Ohm
AES Power Handling (1)	300 W
<b>Maximum Power Handling (2)</b>	<b>600 W</b>
<b>Sensitivity (1W/1m)</b>	<b>97 dB</b>
Frequency Range	35-4000 Hz
<b>Voice Coil Diameter</b>	<b>65 mm (2.56 in)</b>
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	13.2 mm (0.52 in)
<b>Magnetic Gap Depth</b>	<b>8.2 mm (0.32 in)</b>
Flux Density	1.2 T
Magnet	Neodymium Slug
Basket Material	Aluminum
Demodulation	No
Cone Surround (3)	Accordion (4 waves)
NET Air Volume filled by Loudspeaker	3 dm <sup>3</sup> (0.106 ft <sup>3</sup> )
Spider Profile	1x constant height waves

## THIELE & SMALL PARAMETERS

Fs	35 Hz
Re	5.4 Ohm
Qes	0.5
Qms	14.0
Qts	0.48
Vas	220.1 dm <sup>3</sup> (7.77 ft <sup>3</sup> )
Sd	870 cm <sup>2</sup> (134.79 in <sup>2</sup> )
Xmax (4)	5.23 mm
Xdamage (5)	12.3 mm
Mms	99.2 g
Bl	15.6 N/A
Le	0.89 mH
Mmd	70.2 g
Cms	0.21 mm/N
Rms	1.6 kg/s
Eta Zero	1.89 %
EBP	70 Hz

