

12FH520



12" - 600 W - 97 dB - 16 Ohm

NOMINAL SPECIFICATIONS

Nominal Diameter	300 mm (12 in)
Overall Diameter	316 mm (12.44 in)
Bolt Circle Diameter	298.5 mm (11.75 in)
Baffle Cutout Diameter	284 mm (11.18 in)
Depth	155.75 mm (6.13 in)
Flange and Gasket Thickness	12.45 mm (0.49 in)
Net Weight	4.2 kg (9.3 lb)
Shipping Box (Single Carton Box)	350 x 346 x 216 mm (13.8 x 13.6 x 8.5 in)
Shipping Weight	5 kg (11.0 lb)

PART NUMBER

Push Terminals - 16 Ohm Version 03004124

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	16 Ohm
Minimum Impedance	15 Ohm
AES Power Handling (1)	600 W
Maximum Power Handling (2)	1200 W
Sensitivity (1W/1m)	97 dB
Frequency Range	50-4000 Hz
Voice Coil Diameter	77 mm (3 in)
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	18 mm (0.71 in)
Magnetic Gap Depth	12 mm (0.47 in)
Flux Density	1.1 T
Magnet	Neodymium Slug
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround (3)	Triple Roll
NET Air Volume filled by Loudspeaker	2.4 dm ³ (0.085 ft ³)
Spider Profile	1x variable height waves

THIELE & SMALL PARAMETERS

Fs	55 Hz
Re	12.8 Ohm
Qes	0.48
Qms	17
Qts	0.47
Vas	56.4 dm ³ (1.99 ft ³)
Sd	540 cm ² (83.70 in ²)
Xmax (4)	7.00 mm
Xdamage (5)	19.5 mm
Mms	60.5 g
Bl	23.5 N/A
Le	1.6 mH
Mmd	46.3 g
Cms	0.14 mm/N
Rms	1.2 kg/s
Eta Zero	1.88 %
EBP	115 Hz

