

15FH500

15" - 500 W - 98 dB - 8 Ohm



NOMINAL SPECIFICATIONS

Nominal Diameter	380 mm (15 in)
Overall Diameter	393 mm (15.47 in)
Bolt Circle Diameter	374 mm (14.72 in)
Baffle Cutout Diameter	356 mm (14.02 in)
Depth	181.3 mm (7.14 in)
Flange and Gasket Thickness	13.7 mm (0.54 in)
Net Weight	4.3 kg (9.5 lb)
Shipping Box (Single Carton Box)	430 x 427 x 236 mm (16.9 x 16.8 x 9.3 in)
Shipping Weight	5.4 kg (11.9 lb)

PART NUMBER

Push Terminals - 8 Ohm Version	03803926
--------------------------------	----------

NOTES:

PATENTED IT 2006/000327

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	6 Ohm
AES Power Handling (1)	500 W
Maximum Power Handling (2)	1000 W
Sensitivity (1W/1m)	98 dB
Frequency Range	35-3150 Hz
Voice Coil Diameter	77 mm (3 in)
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	22 mm (0.87 in)
Magnetic Gap Depth	10.5 mm (0.41 in)
Flux Density	1.2 T
Magnet	Neodymium Slug
Basket Material	Aluminum
Demodulation	No
Cone Surround (3)	M-Roll
NET Air Volume filled by Loudspeaker	3.4 dm ³ (0.120 ft ³)
Spider Profile	1x variable height waves

THIELE & SMALL PARAMETERS

Fs	35 Hz
Re	5.1 Ohm
Qes	0.32
Qms	10.4
Qts	0.31
Vas	199.2 dm ³ (7.03 ft ³)
Sd	847 cm ² (131.29 in ²)
Xmax (4)	9.25 mm
Xdamage (5)	16 mm
Mms	104.0 g
Bl	19.2 N/A
Le	1.3 mH
Mmd	76.1 g
Cms	0.20 mm/N
Rms	2.2 kg/s
Eta Zero	2.62 %
EBP	109 Hz

