

15FX600



15" - 700 W - 98 dB - 8 Ohm

NOMINAL SPECIFICATIONS

Nominal Diameter	380 mm (15 in)
Overall Diameter	393 mm (15.47 in)
Bolt Circle Diameter	374 mm (14.72 in)
Baffle Cutout Diameter	354 mm (13.94 in)
Depth	194.3 mm (7.65 in)
Flange and Gasket Thickness	13.7 mm (0.54 in)
Net Weight	5.9 kg (13.0 lb)
Shipping Box (Single Carton Box)	430 x 427 x 236 mm (16.9 x 16.8 x 9.3 in)
Shipping Weight	7.2 kg (15.9 lb)

PART NUMBER

Push Terminals - 8 Ohm Version 03804308

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	6.6 Ohm
AES Power Handling (1)	700 W
Maximum Power Handling (2)	1400 W
Sensitivity (1W/1m)	98 dB
Frequency Range	40-3150 Hz
Voice Coil Diameter	77 mm (3 in)
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	26.5 mm (1.04 in)
Magnetic Gap Depth	12 mm (0.47 in)
Flux Density	1.26 T
Magnet	Neodymium Ring
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround (3)	Triple Roll
NET Air Volume filled by Loudspeaker	4.1 dm ³ (0.145 ft ³)
Spider Profile	1x variable height waves

THIELE & SMALL PARAMETERS

Fs	38 Hz
Re	5 Ohm
Qes	0.28
Qms	6.9
Qts	0.27
Vas	128.3 dm ³ (4.53 ft ³)
Sd	864 cm ² (133.92 in ²)
Xmax (4)	11.25 mm
Xdamage (5)	22.9 mm
Mms	142.5 g
Bl	23.2 N/A
Le	1.26 mH
Mmd	113.8 g
Cms	0.12 mm/N
Rms	4.9 kg/s
Eta Zero	2.16 %
EBP	136 Hz

