

10HP1020



10" - 700 W - 96dB - 8 Ohm

NOMINAL SPECIFICATIONS

Nominal Diameter	250 mm (10 in)
Overall Diameter	261 mm (10.28 in)
Bolt Circle Diameter	246 mm (9.69 in)
Baffle Cutout Diameter	232 mm (9.13 in)
Depth	141.3 mm (5.56 in)
Flange and Gasket Thickness	12.5 mm (0.49 in)
Net Weight	5.2 kg (11.5 lb)
Shipping Box (Single Carton Box)	294 x 290 x 203 mm (11.6 x 11.4 x 8.0 in)
Shipping Weight	5.8 kg (12.8 lb)

PART NUMBER

Push Terminals - 8 Ohm Version	02503939
Recone Kit - 8 Ohm Version	R2503939

NOTES:

PATENTED IT 2006/000327

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polyotton
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	7.3 Ohm
AES Power Handling (1)	700 W
Maximum Power Handling (2)	1400 W
Sensitivity (1W/1m)	96 dB
Frequency Range	60-2500 Hz
Voice Coil Diameter	100 mm (4 in)
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	22 mm (0.87 in)
Magnetic Gap Depth	12 mm (0.47 in)
Flux Density	1.3 T
Magnet	Neodymium Slug
Basket Material	Aluminum
Demodulation	No
Cone Surround (3)	M-Roll
NET Air Volume filled by Loudspeaker	2.2 dm ³ (0.078 ft ³)
Spider Profile	2x non-adjacent symmetrical constant height waves

THIELE & SMALL PARAMETERS

Fs	60 Hz
Re	5.5 Ohm
Qes	0.25
Qms	6.5
Qts	0.24
Vas	16.1 dm ³ (0.57 ft ³)
Sd	345 cm ² (53.48 in ²)
Xmax (4)	9.00 mm
Xdamage (5)	18.2 mm
Mms	72.5 g
Bl	24.5 N/A
Le	0.85 mH
Mmd	65.3 g
Cms	0.10 mm/N
Rms	4.2 kg/s
Eta Zero	1.35 %
EBP	240 Hz

