

# 12RS1066

12" - 1000 W - 93 dB - 8 Ohm



## NOMINAL SPECIFICATIONS

Nominal Diameter	300 mm (12 in)
Overall Diameter	316 mm (12.44 in)
Bolt Circle Diameter	298.5 mm (11.75 in)
Baffle Cutout Diameter	282 mm (11.10 in)
Depth	176.5 mm (6.95 in)
Flange and Gasket Thickness	20.2 mm (0.80 in)
<b>Net Weight</b>	<b>6.6 kg (14.6 lb)</b>
Shipping Box (Single Carton Box)	350 x 346 x 216 mm (13.8 x 13.6 x 8.5 in)
Shipping Weight	7.3 kg (16.1 lb)

## PART NUMBER

Push Terminals - 8 Ohm Version	03004219
--------------------------------	----------

## NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) NBR (Rubber)
- (4)  $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

## TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	6.5 Ohm
AES Power Handling (1)	1000 W
<b>Maximum Power Handling (2)</b>	<b>2000 W</b>
<b>Sensitivity (1W/1m)</b>	<b>93 dB</b>
Frequency Range	45-2500 Hz
<b>Voice Coil Diameter</b>	<b>100 mm (4 in)</b>
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	28.9 mm (1.14 in)
<b>Magnetic Gap Depth</b>	<b>12 mm (0.47 in)</b>
Flux Density	1.22 T
Magnet	Neodymium Ring
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround (3)	Half Roll
NET Air Volume filled by Loudspeaker	2.9 dm <sup>3</sup> (0.102 ft <sup>3</sup> )
Spider Profile	2x non-adjacent symmetrical variable height waves

## THIELE & SMALL PARAMETERS

Fs	42 Hz
Re	5 Ohm
Qes	0.34
Qms	13.9
Qts	0.33
Vas	31.5 dm <sup>3</sup> (1.11 ft <sup>3</sup> )
Sd	496 cm <sup>2</sup> (76.88 in <sup>2</sup> )
Xmax (4)	12.45 mm
Xdamage (5)	20.5 mm
Mms	156.5 g
Bl	24.8 N/A
Le	1.35 mH
Mmd	144.0 g
Cms	0.09 mm/N
Rms	3.0 kg/s
Eta Zero	0.67 %
EBP	124 Hz

