

12RS1066



12" - 1000 W - 92 dB - 16 Ohm

NOMINAL SPECIFICATIONS

Nominal Diameter	300 mm (12 in)
Overall Diameter	316 mm (12.44 in)
Bolt Circle Diameter	298.5 mm (11.75 in)
Baffle Cutout Diameter	282 mm (11.10 in)
Depth	176.5 mm (6.95 in)
Flange and Gasket Thickness	20.2 mm (0.80 in)
Net Weight	6.6 kg (14.6 lb)
Shipping Box (Single Carton Box)	350 x 346 x 216 mm (13.8 x 13.6 x 8.5 in)
Shipping Weight	7.3 kg (16.1 lb)

PART NUMBER

Push Terminals - 16 Ohm Version	03004241
---------------------------------	----------

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) NBR (Rubber)
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	16 Ohm
Minimum Impedance	14.5 Ohm
AES Power Handling (1)	1000 W
Maximum Power Handling (2)	2000 W
Sensitivity (1W/1m)	92 dB
Frequency Range	45-2500 Hz
Voice Coil Diameter	100 mm (4 in)
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	28.9 mm (1.14 in)
Magnetic Gap Depth	12 mm (0.47 in)
Flux Density	1.22 T
Magnet	Neodymium Ring
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround (3)	Half Roll
NET Air Volume filled by Loudspeaker	2.9 dm ³ (0.102 ft ³)
Spider Profile	2x non-adjacent symmetrical variable height waves

THIELE & SMALL PARAMETERS

Fs	45 Hz
Re	12 Ohm
Qes	0.46
Qms	11.2
Qts	0.44
Vas	28.4 dm ³ (1.00 ft ³)
Sd	496 cm ² (76.88 in ²)
Xmax (4)	12.45 mm
Xdamage (5)	20.5 mm
Mms	151.5 g
Bl	33.5 N/A
Le	2.5 mH
Mmd	139.0 g
Cms	0.08 mm/N
Rms	3.8 kg/s
Eta Zero	0.55 %
EBP	98 Hz

