

# 18HP1060

18" - 1200 W - 98 dB - 8 Ohm



## NOMINAL SPECIFICATIONS

Nominal Diameter	460 mm (18 in)
Overall Diameter	460 mm (18.11 in)
Bolt Circle Diameter	440 mm (17.32 in)
Baffle Cutout Diameter	422 mm (16.61 in)
Depth	215 mm (8.46 in)
Flange and Gasket Thickness	13.9 mm (0.55 in)
<b>Net Weight</b>	<b>7.3 Kg (16.1 lb)</b>
Shipping Box (Single Carton Box)	503 x 500 x 258 mm (19.8 x 19.7 x 10.2 in)
Shipping Weight	8.7 Kg (19.2 lb)

## PART NUMBER

Push Terminals - 8 Ohm Version	04604053
--------------------------------	----------

## NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4)  $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

## TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	6.3 Ohm
AES Power Handling (1)	1200 W
<b>Maximum Power Handling (2)</b>	<b>2400 W</b>
<b>Sensitivity (1W/1m)</b>	<b>98 dB</b>
Frequency Range	35-1600 Hz
<b>Voice Coil Diameter</b>	<b>100 mm (4 in)</b>
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	28.9 mm (1.14 in)
<b>Magnetic Gap Depth</b>	<b>12 mm (0.47 in)</b>
Flux Density	1.22 T
Magnet	Neodymium Ring
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround (3)	Triple Roll
NET Air Volume filled by Loudspeaker	5.3 dm <sup>3</sup> (0.187 ft <sup>3</sup> )
Spider Profile	2x non-adjacent symmetrical variable height waves

## THIELE & SMALL PARAMETERS

Fs	35 Hz
Re	5 Ohm
Qes	0.38
Qms	11.1
Qts	0.37
Vas	175 dm <sup>3</sup> (6.18 ft <sup>3</sup> )
Sd	1124 cm <sup>2</sup> (174.22 in <sup>2</sup> )
Xmax (4)	12.45 mm
Xdamage (5)	21 mm
Mms	211.8 g
Bl	24.8 N/A
Le	1.26 mH
Mmd	189.1 g
Cms	0.10 mm/N
Rms	4.19 Kg/s
Eta Zero	1.93 %
EBP	92 Hz

