

18HP1030

18" - 1200 W - 98 dB - 4 Ohm



NOMINAL SPECIFICATIONS

Nominal Diameter	460 mm (18 in)
Overall Diameter	460 mm (18.11 in)
Bolt Circle Diameter	440 mm (17.32 in)
Baffle Cutout Diameter	421 mm (16.57 in)
Depth	208.35 mm (8.20 in)
Flange and Gasket Thickness	13.7 mm (0.54 in)
Net Weight	12.1 kg (26.7 lb)
Shipping Box (Single Carton Box)	503 x 500 x 258 mm (19.8 x 19.7 x 10.2 in)
Shipping Weight	13.5 kg (29.8 lb)

PART NUMBER

Push Terminals - 4 Ohm Version	04604092
Recone Kit - 4 Ohm Version	R4604092

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	4 Ohm
Minimum Impedance	3.9 Ohm
AES Power Handling (1)	1200 W
Maximum Power Handling (2)	2400 W
Sensitivity (1W/1m)	98 dB
Frequency Range	35-1600 Hz
Voice Coil Diameter	100 mm (4 in)
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	28.9 mm (1.14 in)
Magnetic Gap Depth	12 mm (0.47 in)
Flux Density	1.1 T
Magnet	Ferrite Ring
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround (3)	Triple Roll
NET Air Volume filled by Loudspeaker	6.5 dm ³ (0.230 ft ³)
Spider Profile	2x non-adjacent symmetrical constant height waves

THIELE & SMALL PARAMETERS

Fs	35 Hz
Re	2.9 Ohm
Qes	0.33
Qms	12.3
Qts	0.32
Vas	172.2 dm ³ (6.08 ft ³)
Sd	1212 cm ² (187.86 in ²)
Xmax (4)	12.45 mm
Xdamage (5)	23.1 mm
Mms	246.3 g
Bl	21.7 N/A
Le	1.08 mH
Mmd	198.6 g
Cms	0.08 mm/N
Rms	4.4 kg/s
Eta Zero	2.15 %
EBP	106 Hz

