

8FE400



8" - 200 W - 96 dB - 4 Ohm

NOMINAL SPECIFICATIONS

Nominal Diameter	200 mm (8 in)
Overall Diameter	209 mm (8.23 in)
Bolt Circle Diameter	197 mm (7.76 in)
Baffle Cutout Diameter	183 mm (7.20 in)
Depth	96 mm (3.78 in)
Flange and Gasket Thickness	7 mm (0.28 in)
Net Weight	2.78 kg (6.1 lb)
Shipping Box (Single Carton Box)	227 x 224 x 113 mm (8.93 x 8.81 x 4.44 in)
Shipping Weight	2.95 kg (6.5 lb)

PART NUMBER

Faston Terminals - 8 Ohm Version 02004429

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	4 Ohm
Minimum Impedance	3.9 Ohm
AES Power Handling (1)	200 W
Maximum Power Handling (2)	400 W
Sensitivity (1W/1m)	96 dB
Frequency Range	100-6000 Hz
Voice Coil Diameter	44 mm (1.73 in)
Winding Material	Al
Former Material	Al
Winding Depth	12.4 mm (0.49 in)
Magnetic Gap Depth	8 mm (0.31 in)
Flux Density	1.10 T
Magnet	Ferrite Ring
Basket Material	Steel
Demodulation	No
Cone Surround (3)	Triple Roll
NET Air Volume filled by Loudspeaker	0.9 dm ³ (0.032 ft ³)
Spider Profile	1x constant height waves

THIELE & SMALL PARAMETERS

Fs	100 Hz
Re	3.4 Ohm
Qes	0.53
Qms	4.8
Qts	0.48
Vas	9.9 dm ³ (0.35 ft ³)
Sd	233 cm ² (36.12 in ²)
Xmax (4)	4.87 mm
Xdamage (5)	15.5 mm
Mms	19.4 g
Bl	8.8 N/A
Le	0.3 mH
Mmd	15.4 g
Cms	0.13 mm/N
Rms	2.5 kg/s
Eta Zero	1.80 %
EBP	187 Hz

