

10FE400



10" - 200 W - 95 dB - 4 Ohm

NOMINAL SPECIFICATIONS

Nominal Diameter	250 mm (10 in)
Overall Diameter	260 mm (10.24 in)
Bolt Circle Diameter	246 mm (9.69 in)
Baffle Cutout Diameter	233 mm (9.17 in)
Depth	111 mm (4.37 in)
Flange and Gasket Thickness	7 mm (0.28 in)
Net Weight	2.95 kg (6.5 lb)
Shipping Box (Single Carton Box)	285 x 285 x 165 mm (11.2 x 11.2 x 6.49 in)
Shipping Weight	3.5 kg (7.7 lb)

PART NUMBER

Faston Terminals - 8 Ohm Version	02504430
----------------------------------	----------

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	4 Ohm
Minimum Impedance	3.7 Ohm
AES Power Handling (1)	200 W
Maximum Power Handling (2)	400 W
Sensitivity (1W/1m)	95 dB
Frequency Range	60-4500 Hz
Voice Coil Diameter	44 mm (1.73 in)
Winding Material	Cu
Former Material	Al
Winding Depth	13.9 mm (0.53 in)
Magnetic Gap Depth	8 mm (0.31 in)
Flux Density	1.10 T
Magnet	Ferrite Ring
Basket Material	Steel
Demodulation	No
Cone Surround (3)	Triple Roll
NET Air Volume filled by Loudspeaker	1.25 dm ³ (0.044 ft ³)
Spider Profile	1x constant height waves

THIELE & SMALL PARAMETERS

Fs	60 Hz
Re	3.2 Ohm
Qes	0.44
Qms	5.2
Qts	0.41
Vas	33.6 dm ³ (1.19 ft ³)
Sd	362 cm ² (56.11 in ²)
Xmax (4)	5.62 mm
Xdamage (5)	14.9 mm
Mms	38.3 g
Bl	10.2 N/A
Le	0.5 mH
Mmd	30.5 g
Cms	0.18 mm/N
Rms	2.8 kg/s
Eta Zero	1.59 %
EBP	135 Hz

