

HF14AT

1.4" - 90 W - 110 dB - 8 Ohm



NOMINAL SPECIFICATIONS

Throat Diameter	35.6 mm (1.4 in)
Overall Diameter	130.5 mm (5.14 in)
90° Mounting Holes Diameter (4xM6)	102 mm (4.02 in)
Depth	62 mm (2.44 in)
Net Weight	3 kg (6.61 lb)
Shipping Box (Single carton box)	185 x 170 x 122 mm (7.3 x 6.7 x 4.8 in)
Shipping Weight	3.2 kg (7.05 lb)

NOTES:

- Driver mounted on **FaitalPRO LTH142 Horn**
(1) 2 Hours Test According to AES 2-1984 Rev. 2003
(2) Maximum power is defined as 3dB greater than nominal power.
(3) 12 dB/oct or higher slope high-pass filter
(4) Averaged within the frequency range

TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	7.2 Ohm
AES Power above 0.9 kHz (1)	90 W
AES Power above 0.65 kHz	50 W
Maximum Power above 0.9 kHz (2)	180 W
Maximum Power above 0.65 kHz	100 W
Minimum Crossover Frequency (3)	0.9 kHz
Sensitivity (1W/1m) (4)	110 dB
Frequency Range	0.5÷18 kHz
Voice Coil Diameter	74 mm (2.91 in)
Winding Material	Al
Former Material	Kapton
Diaphragm Material	Titanium
Diaphragm Shape	Dome
Winding Depth	2.35 mm (0.10 in)
Magnetic Gap Depth	2.80 mm (0.11 in)
Flux Density	1.95 T
Magnet	Neodymium Ring
Re	5.6 Ohm
Phase Plug Design	Annular
NET Air Volume filled by HF Driver	0.7 dm ³ (0.025 ft ³)

