

# HF20AT

2" - 90 W - 110 dB - 16 Ohm



## NOMINAL SPECIFICATIONS

Throat Diameter	50.8 mm (2 in)
Overall Diameter	130.5 mm (5.14 in)
90° Mounting Holes Diameter (4xM6)	102 mm (4.02 in)
Depth	95 mm (3.74 in)
<b>Net Weight</b>	<b>3.3 kg (7.28 lb)</b>
Shipping Box (Single carton box)	185 x 170 x 122 mm (7.3 x 6.7 x 4.8 in)
Shipping Weight	3.5 kg (7.72 lb)

## NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) 12 dB/oct or higher slope high-pass filter
- (4) Averaged within the frequency range

## TECHNICAL PARAMETERS

Nominal Impedance	16 Ohm
Minimum Impedance	10.3 Ohm
<b>AES Power above 0.9 kHz (1)</b>	<b>90 W</b>
AES Power above 0.65 kHz	50 W
<b>Maximum Power above 0.9 kHz (2)</b>	<b>180 W</b>
Maximum Power above 0.65 kHz	100 W
Minimum Crossover Frequency (3)	0.9 kHz
<b>Sensitivity (1W/1m) (4)</b>	<b>110 dB</b>
Frequency Range	0.5÷18 kHz
<b>Voice Coil Diameter</b>	<b>74 mm (2.91 in)</b>
<b>Winding Material</b>	<b>Al</b>
Former Material	Kapton
<b>Diaphragm Material</b>	<b>Titanium</b>
Diaphragm Shape	Dome
Winding Depth	2.35 mm (0.10 in)
Magnetic Gap Depth	2.80 mm (0.11 in)
Flux Density	1.95 T
Magnet	Neodymium Ring
Re	8.2 Ohm
Phase Plug Design	Annular
NET Air Volume filled by HF Driver	1.1 dm <sup>3</sup> (0.039 ft <sup>3</sup> )

