

M6N8-150



6" - 150 W - 94 dB - 8 Ohm

NOMINAL SPECIFICATIONS

Nominal Diameter	160 mm (6 in)
Overall Diameter	186.5/162 mm (7.34/6.37 in)
Bolt Circle Diameter	172 mm (6.77 in)
Baffle Cutout Diameter	145 mm (5.7 in)
Depth	87.2 mm (3.43 in)
Flange and Gasket Thickness	7.5 mm (0.29 in)
Net Weight	1.4 kg (3.08 lb)
Shipping Box (Single Carton Box)	195 x 195 x 141 mm (7.7 x 7.7 x 5.6 in)
Shipping Weight	1.6 kg (3.52 lb)

TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	6.2 Ohm
AES Power Handling (1)	150 W
Maximum Power Handling (2)	300 W
Sensitivity (1W/1m)	94 dB
Frequency Range	100-5000 Hz
Voice Coil Diameter	52 mm (2 in)
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	9.8 mm (0.38 in)
Magnetic Gap Depth	6 mm (0.24 in)
Flux Density	1.35 T

THIELE & SMALL PARAMETERS

Fs	100 Hz
Re	5.3 Ohm
Qes	0.34
Qms	5.8
Qts	0.32
Vas	3.89 dm ³ (0.137 ft ³)
Sd	114 cm ² (17.67 in ²)
Xmax (3)	3.90 mm
Xdamage (4)	11.6 mm
Mms	12 g
Bl	10.8 N/A
Le	0.25 mH
Mmd	11.2 g
Cms	0.21 mm/N
Rms	1.45 kg/s
Eta Zero	1.1 %

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Xmax= [(winding depth - magnetic gap depth)/2] + (magnetic gap depth/3)
- (4) Maximum excursion before permanent damage

