

12FX600



12" - 700 W - 97 dB - 8 Ohm

NOMINAL SPECIFICATIONS

Nominal Diameter	300 mm (12 in)
Overall Diameter	316 mm (12.44 in)
Bolt Circle Diameter	298.5 mm (11.75 in)
Baffle Cutout Diameter	282 mm (11.10 in)
Depth	168.75 mm (6.64 in)
Flange and Gasket Thickness	12.45 mm (0.49 in)
Net Weight	5.5 kg (12.1 lb)
Shipping Box (Single Carton Box)	350 x 346 x 216 mm (13.8 x 13.6 x 8.5 in)
Shipping Weight	6.2 kg (13.7 lb)

PART NUMBER

Push Terminals - 8 Ohm Version	03004307
Recone Kit - 8 Ohm Version	R3004307

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	6.5 Ohm
AES Power Handling (1)	700 W
Maximum Power Handling (2)	1400 W
Sensitivity (1W/1m)	97 dB
Frequency Range	50-3150 Hz
Voice Coil Diameter	77 mm (3 in)
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	23.8 mm (0.94 in)
Magnetic Gap Depth	12 mm (0.47 in)
Flux Density	1.26 T
Magnet	Neodymium Ring
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround (3)	Triple Roll
NET Air Volume filled by Loudspeaker	2.9 dm ³ (0.102 ft ³)
Spider Profile	1x variable height waves

THIELE & SMALL PARAMETERS

Fs	48 Hz
Re	5.3 Ohm
Qes	0.25
Qms	6.88
Qts	0.24
Vas	44.4 dm ³ (1.57 ft ³)
Sd	538 cm ² (83.39 in ²)
Xmax (4)	9.90 mm
Xdamage (5)	24.1 mm
Mms	100 g
Bl	25.3 N/A
Le	1.34 mH
Mmd	85.9 g
Cms	0.11 mm/N
Rms	4.4 kg/s
Eta Zero	1.91 %
EBP	192 Hz

